


Models

☐ FSS-FL

☐ FSS-PT

☐ FSE-FL

☐ FSE-PT

☐ FST-PT


FSS-FL

Standard Features:

- Fully 304 stainless steel construction
- Easy-to-remove & clean parts
- Highly durable & reliable ceramic heating elements
- Special design bottom heater for dump pan heating
- Divider could optionally to segregate different product placed in the dump pan.
- Raised edge around dump basket and pre-pack area for easier cleaning
- Poly carbonate shield for pre-pack to keep packed fries fresh & warm
- Low wattage rating & less energy consumption


Options & Accessories

- GN pan 1/3 size, 6" deep
- GN pan 1/6 size, 6" deep
- French fries rack


Specifications:

This innovative Fries Warmer doubles your fried food-holding time and keeps your fries golden looking & crispy tasting just like they were straight out from the fryer. Uniquely developed for the Quick Serve market, the fries Warmer combines intense ceramic radiant heat technologies and a specially designed bottom heat source to extend the freshness for a variety of fried foods including nuggets & wedges, thus keeping all those fried foods moist and delicious for up to 20 minutes without drying or creating a limp product. Optional SMART product timer allows operators to monitor and track each individual product's shelf, thus improving food quality, consistency and safety issues.


FSSFL




FSEFL







FSSPT/FSEPT






FSTPT



Plan



Front



Section

Feature	Product Code	Part Number	Dimension (mm)			Electrical Data					Shipping Weight (kg)
			Width	Depth	Height	Volt	Phase	Hertz	Watts	Amps	
Standard front loading	FSS-FL	F70-180	1010	720	1500	230	1	50	2390	10.4	100
Express front loading	FSE-FL	F91-313	500	720	1500	230	1	50	1870	8.1	80
Standard Pass Through	FSS-PT	F91-388	920	850	1500	230	1	50	2390	10.4	100
Express Pass Through	FSE-PT	F91-382	610	750	1450	230	1	50	1870	8.1	80
Twin Pass Through	FST-PT	F91-354	600	1280	1450	230	1	50	2390	10.4	100